



LED-driver with integrated individual lamp monitoring for non-maintained, maintained and switched-maintained lighting. With integrated charging technology and freely selectable nominal operating time of 1h, 1,5h, 2h, 3h or 8h with INOTEC SV/B- function control to connect to a central monitoring device BNS-MTB according to DIN EN 50172, DIN VDE 0100-718 and DIN VDE V 0108-100-1.

Luminaire including test button for manual function and duration test with detailed LED status- and charge control indicator.

Complying with the international standards for safety and working, electromagnetic compatibility and interference resistance for high function safety. LED output dimmable continuously in mains operation.

## Technical details

<b>Material</b>	polycarbonate
<b>Permitted temperature range</b>	M: -5...+35 °C, NM: 0...+40 °C
<b>Apparent power</b>	7.5 VA
<b>Input terminal</b>	max. 2,5mm <sup>2</sup> single-core
<b>Battery capacity</b>	1.1 Ah
<b>Rated duration</b>	1h;1,5h;2h;3h;8h
<b>Battery</b>	Ni-MH

## EB LED SV/B 1-8/D modul

Art. no.: 101418045

<b>Nominal voltage AC</b>	230V AC $\pm$ 10% 50/60 Hz
<b>Type of current</b>	constant current
<b>Dim.</b>	Length x Width x Height: 41 mm x 111 mm x 32 mm
<b>Output current</b>	320 mA