


Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side. Suitable for the usage in outdoor areas due to an outsourced supply unit.

External supply unit: IP66; Ta: -5...+40 °C


**Technical data**

<b>Rated duration:</b>	1h;1,5h;2h;3h;8h	<b>Effective power:</b>	5,0 W
<b>Battery type:</b>	Ni-MH 4,8 V 1,1 Ah	<b>Inrush current:</b>	11 A / 64 µs
<b>Material:</b>	die-cast aluminum powder-coated	<b>Protection class:</b>	III
<b>Illuminant:</b>	18 x 0,32W LED-module	<b>Input terminals:</b>	max. 2,5mm <sup>2</sup> single-core
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current AC:</b>	26 mA	<b>Impact resistance:</b>	IK09
<b>Apparent power:</b>	6,0 VA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
<b>1h</b>	65%					
1.0	2.3	5.6	1.9	5.2	0.0	0.0
2.0	3.2	7.8	3.1	7.8	2.5	7.1
3.0	3.7	9.2	3.6	9.3	3.2	8.9
4.0	3.9	10.1	3.9	10.4	3.6	10.1
5.0	3.9	10.7	4.0	11.0	3.7	10.8
<b>3h</b>	30%					
1.0	1.8	4.5	1.1	3.6	0.0	0.0
2.0	2.5	6.2	2.1	5.9	0.9	4.7
3.0	2.7	7.2	2.5	7.0	1.7	6.2
4.0	2.6	7.6	2.4	7.5	1.6	6.9
5.0	2.1	7.5	1.9	7.5	0.6	6.9
<b>8h</b>	15%					
1.0	1.2	4.0	0.0	0.0	0.0	0.0
2.0	1.5	3.4	0.0	0.0	0.0	0.0
3.0	1.1	5.5	0.0	0.0	0.0	0.0


**Articles**
**BN/V 6201 -03 SV/B LED 1-8/D**

Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104366542	104366744	104366340	104366239	104366643	104366845

wall mounting


Light colour: 3000 K

Protection category: IP65


**BN-supply AP SV/B LED - 1-8/DSKII IP66**

Art. no. 102024091

required



Name	Accessories	Art. no.
BN-supply AP SV/B LED - 1-8/DSKII IP66	required	102024091
mounting adapter 6201 RAL 7015	optional	104575292