




Explosion-protected safety and escape sign luminaire for Zone 2, 22. Luminaires for ceiling or wall surface mounting. Housing made of die-cast aluminium with moulded mounting brackets.



Technical data

viewing distance:	22 m	Effective power:	2,8 W
Material:	die-cast aluminum	Protection class:	I
Illuminant:	6 X 0,5w LED-module	Input terminals:	2.5mm ² feed through wiring
Luminous flux:	150 lm	Temperature ta:	-20...+40 °C
Nominal voltage DC:	24 V ±25 %	Impact resistance:	IK10
Nominal current DC:	135 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Distance (m)	1.0lx	1.5lx	2.0lx	2.5lx	3.0lx
2,5	3,0	7,7	7,9	3,0	3,0
3,0	3,1	8,1	8,3	3,0	3,0
4,0	3,0	8,6	8,7	2,9	2,9
5,0	2,5	8,5	8,7	2,4	2,4
6,0	1,1	8,0	8,1	1,1	1,1

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance (m)	1.0lx	1.5lx	2.0lx	2.5lx	3.0lx
2,5	2,2	6,8	6,8	2,2	2,2
3	2,4	7,1	7,1	2,4	2,4
4	2,5	7,7	7,7	2,5	2,5
5	2,3	8,1	8,1	2,3	2,3
6	2,0	8,1	8,1	2,0	2,0
7	1,2	8,2	8,2	1,2	1,2

Articles

EX 7103 D/W LED 24V		Name	Accessories	Art. no.
Colors	Aluminium	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	104747973	LM 24x140 6/6,5K KL	spare part	104770912
wall or ceiling mounting	Light colour: 6500 K	Set of pictograms EX 7103PU,PL,PR		104769595
	Protection category: IP65			



Info:

