




Explosion-protected safety and escape sign luminaire for Zone 2, 22. Luminaires for ceiling or wall surface mounting. Housing made of die-cast aluminium with moulded mounting brackets.



Technical data

viewing distance:	22 m	Apparent power:	5,0 VA
Material:	die-cast aluminum	Effective power:	3,7 W
Illuminant:	6 X 0,5w LED-module	Inrush current:	6 A / 98 µs
Luminous flux:	140 lm	Protection class:	I
Nominal voltage AC:	230V ±10% 50/60 Hz	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	176 - 264 V	Temperature ta:	-20...+40 °C
Nominal current AC:	22 mA	Impact resistance:	IK10
Nominal current DC:	21 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	2,5	3,0	3,0	3,0	3,0
2,5	3,0	7,7	7,9	3,0	
3,0	3,1	8,1	8,3	3,0	
4,0	3,0	8,6	8,7	2,9	
5,0	2,5	8,5	8,7	2,4	
6,0	1,1	8,0	8,1	1,1	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Mounting height (m)	2,5	2,2	6,8	6,8	2,2
3	2,4	7,1	7,1	2,4	
4	2,5	7,7	7,7	2,5	
5	2,3	8,1	8,1	2,3	
6	2,0	8,1	8,1	2,0	
7	1,2	8,2	8,2	1,2	

Articles

EX 7103 D/W LED J/SV

Colors	Aluminium
Art. no.	104748983
wall or ceiling mounting	Light colour: 6500 K Protection category: IP65



Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
LM 24x140 6/6,5K KL	spare part	104770912
Set of pictograms EX 7103PU,PL,PR		104769595

Info:

