

Combined luminaire for general and emergency lighting Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side. Incl. four cable entries for through-wiring to general and emergency lighting.



**Technical data**


<b>Material:</b>	die-cast aluminum powder-coated
<b>Illuminant:</b>	24 x 0,32W + 9 x 0,32W LED-module
<b>Luminous flux:</b>	360 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	36 mA
<b>Nominal current DC:</b>	24 mA

<b>Apparent power:</b>	8,3 VA
<b>Effective power:</b>	5,7 W
<b>Inrush current:</b>	6 A / 34 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK09

**Technical data (General lighting)**

<b>Nominal voltage AC:</b>	230V AC/DC ±10% 50/60 Hz
<b>Apparent power:</b>	12,5 VA
<b>Effective power:</b>	10,4 W

<b>Light colour:</b>	3000 K
<b>Luminous flux:</b>	918 lm
<b>inrush current:</b>	8 A / 50 µs




Wall mounting: Minimum illumination 1.0lx

Distance to middle of escape route	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.6	6.3	2.4	6.1	1.1	4.7
1.5	3.2	7.7	3.1	7.7	2.5	7.0
2.0	3.6	8.8	3.6	8.9	3.2	8.5
2.5	4.0	9.7	4.0	9.9	3.7	9.6
3.0	4.3	10.5	4.3	10.7	4.2	10.5
3.5	4.5	11.1	4.5	11.4	4.3	11.2
4.0	4.6	11.7	4.7	12.0	4.5	11.9
4.5	4.8	12.2	4.8	12.5	4.7	12.4
5.0	4.8	12.6	4.9	12.9	4.8	12.9
5.5	4.9	12.9	5.0	13.2	4.8	13.2
6.0	4.9	13.1	5.0	13.5	4.9	13.5


**Articles**

SN/A 6201 FLD 230V						
Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104353913	104354115	104353711	104353610	104354014	104354216

wall mounting      Light colour: 3000 K      Protection category: IP65



**mounting adapter 6201 RAL 7015**      Art. no. 104575292



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
LM 176x20 24+9/3K KL	spare part	104411911
mounting adapter 6201 RAL 7015	optional	104575292