

Combined luminaire for general and emergency lighting Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side. Incl. four cable entries for through-wiring to general and emergency lighting.




### Technical data

<b>Material:</b>	die-cast aluminum powder-coated	<b>Protection class:</b>	III
<b>Illuminant:</b>	24 x 0,32W + 9 x 0,32W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Luminous flux:</b>	360 lm	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Impact resistance:</b>	IK09
<b>Nominal current DC:</b>	185 mA		

### Technical data (General lighting)

<b>Nominal voltage AC:</b>	230V AC/DC ±10% 50/60 Hz	<b>Light colour:</b>	3000 K
<b>Apparent power:</b>	12,5 VA	<b>Luminous flux:</b>	918 lm
<b>Effective power:</b>	10,4 W	<b>inrush current:</b>	8 A / 50 µs



Wall mounting: Minimum illumination 1.0lx

Distance to middle of escape route	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.6	6.3	2.4	6.1	1.1	4.7
1.5	3.2	7.7	3.1	7.7	2.5	7.0
2.0	3.6	8.8	3.6	8.9	3.2	8.5
2.5	4.0	9.7	4.0	9.9	3.7	9.6
3.0	4.3	10.5	4.3	10.7	4.2	10.5
3.5	4.5	11.1	4.5	11.4	4.3	11.2
4.0	4.6	11.7	4.7	12.0	4.5	11.9
4.5	4.8	12.2	4.8	12.5	4.7	12.4
5.0	4.8	12.6	4.9	12.9	4.8	12.9
5.5	4.9	12.9	5.0	13.2	4.8	13.2
6.0	4.9	13.1	5.0	13.5	4.9	13.5

### Articles


#### SN/A 6201 LED 24V

Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104352596	104352701	104352394	104352293	104352600	104352802

wall mounting


Light colour: 3000 K

Protection category:  
IP65



#### mounting adapter 6201 RAL 7015

Art. no. 104575292



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 176x20 24+9/3K KL	spare part	104411911
mounting adapter 6201 RAL 7015	optional	104575292