

**230V****SN 6114.1 G** Wall, floor and stair luminaires

For connection to FUSION central battery- or emergency power (NEA) systems




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

**Technical data**


<b>Material:</b>	die-cast aluminium
<b>Illuminant:</b>	18 x 0,15W LED-module
<b>Luminous flux:</b>	60 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	34 mA
<b>Nominal current DC:</b>	22 mA

<b>Apparent power:</b>	7,8 VA
<b>Effective power:</b>	5,0 W
<b>Inrush current:</b>	6 A / 34 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C

**Articles****SN 6114.1 FLD 230V**


Colors	RAL 9005	RAL (special)
Art. no.	104435048	104435149

recessed wall or stair mounting    Light colour: 3000 K    Protection category: IP54

**SN 6114.1 FLD 230V**

Colors	RAL 9005	RAL (special)
Art. no.	104436260	104436361

recessed wall or stair mounting    Light colour: 4000 K    Protection category: IP54



Name	Accessories	Art. no.
LM 176x20 18/3K KL	Ersatzteil	104412113
LM 176x20 18/4K KL	Ersatzteil	104412012

