

230V**SN 6114.1 O** Wall, floor and stair luminaires

For connection to FUSION central battery- or emergency power (NEA) systems




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data


| | |
|----------------------------|-----------------------|
| Material: | die-cast aluminium |
| Illuminant: | 18 x 0,15W LED-module |
| Luminous flux: | 169 lm |
| Nominal voltage AC: | 230V ±10% 50/60 Hz |
| Nominal voltage DC: | 176 - 264 V |
| Nominal current AC: | 34 mA |
| Nominal current DC: | 22 mA |

| | |
|--------------------------|--|
| Apparent power: | 7,8 VA |
| Effective power: | 5,0 W |
| Inrush current: | 6 A / 34 µs |
| Protection class: | I |
| Input terminals: | 2.5mm ² feed through wiring |
| Temperature ta: | -15...+40 °C |

**Articles****SN 6114.1 FLD 230V**


| | | |
|----------|-----------|---------------|
| Colors | RAL 9005 | RAL (special) |
| Art. no. | 104435250 | 104435351 |

recessed wall or stair mounting Light colour: 3000 K Protection category: IP54

**SN 6114.1 FLD 230V**

| | | |
|----------|-----------|---------------|
| Colors | RAL 9005 | RAL (special) |
| Art. no. | 104436462 | 104436563 |

recessed wall or stair mounting Light colour: 4000 K Protection category: IP54



| Name | Accessories | Art. no. |
|--------------------|-------------|-----------|
| LM 176x20 18/3K KL | Ersatzteil | 104412113 |
| LM 176x20 18/4K KL | Ersatzteil | 104412012 |

