




Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	18 x 0,15W LED-module
Luminous flux:	358 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	34 mA
Nominal current DC:	22 mA

Apparent power:	7,8 VA
Effective power:	5,0 W
Inrush current:	6 A / 34 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK09



Wall mounting: Minimum illumination 1.0lx


Distance to middle of escape route	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.6	6.3	2.4	6.1	1.1	4.7
1.5	3.2	7.7	3.1	7.7	2.5	7.0
2.0	3.6	8.8	3.6	8.9	3.2	8.5
2.5	4.0	9.7	4.0	9.9	3.7	9.6
3.0	4.3	10.5	4.3	10.7	4.2	10.5
3.5	4.5	11.1	4.5	11.4	4.3	11.2
4.0	4.6	11.7	4.7	12.0	4.5	11.9
4.5	4.8	12.2	4.8	12.5	4.7	12.4
5.0	4.8	12.6	4.9	12.9	4.8	12.9
5.5	4.9	12.9	5.0	13.2	4.8	13.2
6.0	4.9	13.1	5.0	13.5	4.9	13.5

Articles


SN 6201 -03 FLD 230V

Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104358155	104358357	104357953	104357852	104358256	104358458

wall mounting Light colour: 3000 K Protection category: IP65



mounting adapter 6201 RAL 7015 Art. no. 104575292



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
LM 176x20 18/3K KL	spare part	104412113
mounting adapter 6201 RAL 7015	optional	104575292