


Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side.



### Technical data

<b>Material:</b>	die-cast aluminum powder-coated	<b>Protection class:</b>	III
<b>Illuminant:</b>	18 x 0,15W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Luminous flux:</b>	358 lm	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Impact resistance:</b>	IK09
<b>Nominal current DC:</b>	175 mA		



Wall mounting: Minimum illumination 1.0lx

Distance to middle of escape route	Distance to middle of escape route					
	1.0m	2.0m	3.0m	4.0m	5.0m	6.0m
1.0	2.6	6.3	2.4	6.1	1.1	4.7
1.5	3.2	7.7	3.1	7.7	2.5	7.0
2.0	3.6	8.8	3.6	8.9	3.2	8.5
2.5	4.0	9.7	4.0	9.9	3.7	9.6
3.0	4.3	10.5	4.3	10.7	4.2	10.5
3.5	4.5	11.1	4.5	11.4	4.3	11.2
4.0	4.6	11.7	4.7	12.0	4.5	11.9
4.5	4.8	12.2	4.8	12.5	4.7	12.4
5.0	4.8	12.6	4.9	12.9	4.8	12.9
5.5	4.9	12.9	5.0	13.2	4.8	13.2
6.0	4.9	13.1	5.0	13.5	4.9	13.5

### Articles


#### SN 6201 -03 LED 24V

Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104356741	104356943	104356539	104356438	104356842	104357044

wall mounting


Light colour: 3000 K

Protection category:  
IP65



#### mounting adapter 6201 RAL 7015

Art. no. 104575292



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 176x20 18/3K KL	spare part	104412113
mounting adapter 6201 RAL 7015	optional	104575292