




Downlight for enhanced lighting requirements. For illuminating workplaces with special risks, swimming pools or sports facilities. Robust, chlorine-resistant housing made of die-cast aluminium with optional lateral cable gland.



Technical data

<b>Material:</b>	die-cast aluminum
<b>Illuminant:</b>	1 x 25W LED-module
<b>Luminous flux:</b>	3401 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	134 mA
<b>Nominal current DC:</b>	135 mA

<b>Apparent power:</b>	30,9 VA
<b>Effective power:</b>	28,4 W
<b>Inrush current:</b>	11 A / 68 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10




Articles

SN 8500 -25 FMD 230V		
Colors	HWF 9006	HWF (special)
Art. no.	101390056	101390157



ceiling mounting      Light colour: 4000 K      Protection category: IP65

Ringbolts for SN 8500/24xx      Art. no. 100912635



Recessed ceiling frame SN 8500, HWF 9006      Art. no. 101432593

Wall bracket SN 8500, RAL 9006      Art. no. 101432795



<b>Name</b>	<b>Accessories</b>	<b>Art. no.</b>
Haube SN 8500	spare part	50207
LED driver replacement SN 8500-25	spare part	101484026
LM 24x24 1/4K PADS	spare part	104440304
M20 cable glands (PU 2 pcs.)	optional	104661784
Recessed ceiling frame SN 8500, HWF 9006	optional	101432593
Recessed ceiling frame SN 8500, HWF SC		101432492
Ringbolts for SN 8500/24xx	optional	100912635
Wall bracket SN 8500, RAL 9006	optional	101432795