


24V

SN 9024.1-03 ALB Downlights

For connection to INOTEC systems with 24V circuits




Discreet LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium cover with a diameter or edge length of no more than 45mm. Luminaire incl. driver for installation in ceiling cut-out of Ø 38mm.



Technical data

Illuminant:	1 x 0,9W LED-module
Luminous flux:	121 lm
Nominal voltage DC:	24 V ±25 %
Nominal current DC:	80 mA

Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C





Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	⊘	⊘	⊘	⊘
2.5	6.9	17.4	5.0	1.7
3.0	6.3	18.9	5.0	1.6
3.5	5.5	19.3	4.9	1.4
4.0	3.9	18.5	4.7	1.1
4.5	2.8	16.9	4.4	0.2

Articles

SN 9024.1 -03 ALB LED 24V round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102477365	102476557	102476759
recessed ceiling mounting	Light colour: 4000 K	Protection category: IP20	

SN 9024.1 -03 ALB LED 24V square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	104310362	104310261	104310463
recessed ceiling mounting	Light colour: 4000 K	Protection category: IP20	



ILD-Supply 24/4-CC-320 L ext.	Art. no. 104182444
required	

Name	Accessories	Art. no.
ILD-Supply 24/4-CC-320 L ext.	required	104182444
LM 24x21 1(3V)/4K KB300	Ersatzteil	104585804

