

LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Housing made of powder-coated aluminium for installation in Ø 68mm ceiling cutout. Incl. 4-chip LED illuminant for maximum safety.



Technical data


Material:	die-cast aluminum powder-coated	Apparent power:	12,5 VA
Illuminant:	1 x 7,1W LED-module	Effective power:	10,9 W
Luminous flux:	978 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	II
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	54 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	49 mA		

Articles

SN 9400 -12 LED J/SV round


Colors	RAL 9005	RAL 9016	RAL 9016	RAL (special)
Art. no.	102307415	101325994	104436967	102488075

recessed ceiling mounting Light colour: 4000 K Protection category: IP20



LED-Supply 230-7 J-SV SK IIext.

Art. no. 101435930



Name	Accessories	Art. no.
FLD-Supply 230/650 SK II ext.		101445428
LED-Supply 230-7 J-SV SK IIext.		101435930
LED-Supply 24-7 S SK II ext.		101436334
LM 39x39 1(12V)/4K KB250 LED Modul	spare part	104556195